


NON-SKINNING BUTYL  
SEALANT APPLIED TO  
ENDS OF ZEE CLOSURE

FIELD NOTCH  
ZEE CLOSURE  
AT RIB



SECTION X-X

3/16"x7/8" BUTYL TAPE

CONSTRUCTION SEALANT  
(NOT BY AEP-SPAN)

CONTINUOUS 3/8"  
BEAD NON-SKINNING  
BUTYL SEALANT

REGLET FLASHING\*  
(RG145: 4")  
(RG147: 5")  
(RG149: 6")

ENGINEERED  
FASTENER  
(NOT BY AEP-SPAN)

HEAD WALL FLASHING\*\*  
(PB119: 10")  
(PB121: 12")  
(PB123: 8")  
(PB125: 10 1/2")

90° HAND CRIMP  
10"  
3/16"x7/8"  
CONT. BUTYL TAPE

NOTE:  
FIRST 10" OF PANEL DOWNHILL OF  
HEADWALL FLASHING WILL NEED TO  
BE 180° HAND CRIMPED TO GET  
SEAMER ON/OFF.

1/4-14 X 7/8" HWH  
W/NEO. WASHER PAINTED  
@ RIBS AND MIN. (1)  
BETWEEN RIBS OR  
MAX. 9" CTRS.

ZEE CLOSURE  
(ZC221)

FASTENER AS REQUIRED

18GA. CONT PANEL  
END SUPPORT  
(SL2ES2)



SPANSEAM

HEAD WALL - FLOATING

SPS-14