


NON-SKINNING BUTYL SEALANT APPLIED TO ENDS OF ZEE CLOSURE

FIELD NOTCH ZEE CLOSURE AT RIB



INSTALLATION NOTE:
CLOSE HEM OF PANELS WITH DUCK BILLS TO ALLOW NOTCHED ZEE CLOSURE TO FIT TIGHTLY TO PANEL

SECTION X-X

3/16"x7/8" BUTYL TAPE

CONSTRUCTION SEALANT (NOT BY AEP-SPAN)

CONTINUOUS 3/8" BEAD NON-SKINNING BUTYL SEALANT

REGLET FLASHING*
(RG145: 4")
(RG147: 5")
(RG149: 6")

HEAD WALL FLASHING**
(PB119: 10")
(PB121: 12")
(PB123: 8")
(PB125: 10 1/2")

ENGINEERED FASTENER (NOT BY AEP-SPAN)

3/16"x7/8" CONT. BUTYL TAPE

1/4-14 X 7/8" HWH SCOTS W/NEO. WASHER PAINTED @ RIBS AND MIN. (1) BETWEEN RIBS OR MAX. 9" CTRS.

ZEE CLOSURE (ZC221)

FASTENER AS REQUIRED

18GA. CONT PANEL END SUPPORT (SL2ES2)



SPAN-LOK hp

HEAD WALL - FLOATING

SL-14